

ASKOMA *we care about energy*



PLUG DISCONNECTION SET

THE SOLUTION FOR FAST, ERROR-FREE SERVICE WORK
E.G. IN THE DRINKING WATER TANK



- For the **ASKOHEAT** screw-in heater
- For the **ASKOHEAT-F** flange heater

ORDER OPTIONS

The plug disconnection set is designed to make your work easier and save time when servicing the heating element.

It allows you to disconnect the heating element from the mains quickly and easily.

All you have to do is disconnect the connection cable and reconnect it later.

The plug disconnection set saves you time during the recurring descaling of the heating element in the drinking water tank.

Once the plug disconnect set has been installed, the end customer is offered a solution that is fast, error-free, cost-effective and does not require a new electrical specialist consultation.

In the following table you will find your existing heating element model by article number or type and the corresponding plug and disconnect set:

Order no.	Quantity	For the following article no.	For the following types	Type of construction	max. power
-----------	----------	-------------------------------	-------------------------	----------------------	------------

1.1. Plug disconnect set for ASKOHEAT screw-in heater

	012-2261	1 x	012-47XX	Type S	Insulated mounting	up to 9.0 kW
	012-2261	1 x	012-45XX	Type W	Insulated mounting	up to 9.0 kW
	012-2261	1 x	012-46XX	Type O	Insulated mounting	up to 9.0 kW
	012-2261	1 x	012-55XX	Type OP	Insulated mounting	up to 9.0 kW
	012-2261	1 x	012-57XX	Type SE	Insulated mounting	up to 3.0 kW
	012-2261	1 x	012-32XX	Type A	Soldered	up to 9.0 kW
	012-2261	1 x	012-34XX	Type S	Soldered	up to 9.0 kW
	012-2261	1 x	012-35XX	Type W	Soldered	up to 9.0 kW
	012-2261	1 x	012-36XX	Type O	Soldered	up to 9.0 kW

1.2. Plug disconnect set for ASKOHEAT-F, flange heater Ø 180/240/280mm

	012-2261	1 x	012-16XX	Type A	Insulated mounting ^{1 x}	up to 10.0 kW
	012-2261	1 x	012-168X	Type D	Insulated mounting	up to 10.0 kW
	012-2261	1 x	012-15XX	Type W	Insulated mounting	up to 10.0 kW
	012-2261	1 x	012-56XX	Type OP	Insulated mounting	up to 10.0 kW
	012-2261	1 x	012-58XX	Type SE	Insulated mounting	up to 3.0 kW
	012-2261	2 x	012-17XX	Type A	Insulated mounting	up to 20.0 kW
	012-2261	2 x	012-18XX	Type A	Insulated mounting	up to 20.0 kW

1.3. Plug disconnect set for ASKOHEAT screw-in heater

	012-2262	1 x	012-44XX	Type C	Insulated mounting	up to 9.0 kW
	012-2262	1 x	012-614X	Type PV2	Insulated mounting	up to 9.0 kW
	012-2262	1 x	012-616X	Type PV4	Insulated mounting	up to 9.0 kW
	012-2262	1 x	012-33XX	Type B	Soldered	up to 9.0 kW
	012-2262	1 x	012-31XX	Type BZ	Soldered	up to 9.0 kW
	012-2262	1 x	012-34XX	Type C	Soldered	up to 9.0 kW

1.4. Plug disconnect set for ASKOHEAT-F, flange heater Ø 180/240/280mm

	012-2262	1 x	012-13XX	Type B	Insulated mounting	up to 10.0 kW
	012-2262	1 x	012-14XX	Type C	Insulated mounting	up to 10.0 kW
	012-2262	1 x	012-165X	Type E	Insulated mounting	up to 15.0 kW
	012-2262	1 x	012-664X	Type PV2	Insulated mounting	up to 10.0 kW
	012-2262	1 x	012-666X	Type PV4	Insulated mounting	up to 10.0 kW
	012-2262 012-2261	each 1 x	012-17XX	Type E	Insulated mounting	up to 25.0 kW
	012-2262 012-2261	each 1 x	012-18XX	Type E	Insulated mounting	up to 25.0 kW

ATTENTION:

- for flange inserts Ø 240mm and 280mm **type A**, you need two plug disconnect sets **012-2261**
- for flange inserts Ø 240mm and 280mm **type E**, you need one plug disconnect set **012-2261 and 012-2262**